LUPOY GN5008HF, LUPOY GN5008HFT

Yellow Card™

LG CHEM LTD
128 Yeoui-daero Yeongdeungpo-gu
Seoul, Seoul 07336 Republic of Korea

File Number: E67171

LUPOY GN5008HF, LUPOY GN5008HFT

Polycarbonate (PC)/Acrylonitrile Butadiene Styrene (ABS), pellets

c UL us
ALSO CERTIFIED TO IEC REQUIREMENTS

Flammability	Value	Test Method
Flame Rating		UL 94 IEC 60695-11-10, -20
1.0 mm, NC	V-2	
1.5 mm, ALL	V-0, 5VB	
2.0 mm, ALL	V-0, 5VB	
3.0 mm, ALL	V-0, 5VB	
Thermal	**Value**	**Test Method**
RTI Elec		UL 746B
1.0 mm	60.0 °C	
1.5 mm	60.0 °C	
2.0 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746B
1.0 mm	60.0 °C	
1.5 mm	60.0 °C	
2.0 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Str		UL 746B
1.0 mm	60.0 °C	
1.5 mm	60.0 °C	
2.0 mm	60.0 °C	
3.0 mm	60.0 °C	

Form Number: E67171-248472

UL LLC Copyright ©2024. All rights reserved. | www.ul.com

Report Date: 2/1/2001
Last Revised: 12/13/2022 2:42:07 AM

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.